

M A T E R I A L S A F E T Y D A T A S H E E T

FS-5650

Page 1 of 8

PRODUCT NAME: URETHANE REDUCER FAST
 PRODUCT CODE: FS-5650

HMIS CODES: H F R P
 2*3 0 G

===== SECTION I - MANUFACTURER IDENTIFICATION =====



Manufacturer's Name: 5-Star Autobody Products
 9419 E. San Salvador Drive
 Suite #104
 Scottsdale, AZ 85258

Emergency Telephone: (800) 424-9300
 (CHEMTREC)
 Information Telephone: (480) 451-4451

D.O.T. Hazardous Classification : Paint,
 Flammable Liquid
 UN 1263

Revised on: March 10, 2003

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE mm Hg @ TEMP	WEIGHT PERCENT
ACETONE ACGIH TLV STEL: 750 ppm ACGIH TLV TWA: 500 ppm OSHA VPEL TWA: 750 ppm OSHA VPEL STEL: 1000 ppm	67-64-1	185 68 F	35-40%
* TOLUENE; METHYLBENZENE ACGIH TLV: 150 ppm STEL (SKIN) ACGIH TLV: 50 ppm TWA (SKIN) OSHA VPEL: 150 ppm STEL OSHA VPEL: 100 ppm TWA	108-88-3	22 68 F	13%
2-(1-METHOXY)PROPYL ACETATE	108-65-6	3.68 68 F	10-15%
iso-BUTYL ACETATE	110-19-0	18.0 68 F	5-10%

M A T E R I A L S A F E T Y D A T A S H E E T

FS-5650

Page 2 of 8

OSHA TWA VPEL: 150 ppm
ACGIH TWA TLV: 150 ppm

M A T E R I A L S A F E T Y D A T A S H E E T

FS-5650

Page 3 of 8

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE mm Hg @ TEMP		WEIGHT PERCENT
LIGHT ALIPHATIC NAPHTHA 400PPM TLV 400PPM PEL	64742-89-8	60.0	68 F	0-10%
n-HEPTANE OSHA PEL: 400 ppm TWA OSHA PEL: 500 ppm STEL ACGIH TLV: 400 ppm TWA ACGIH TLV: 500 ppm STEL	142-82-5	76	68 F	5-10%
n-BUTYL ACETATE ACGIH TLV TWA: 150 ppm ACGIH TLV STEL: 200 ppm OSHA VPPEL TWA: 150 ppm OSHA VPPEL STEL: 200 ppm	123-86-4	8.4	68 F	0-5%
* XYLENE ACGIH TWA 100 ppm ACGIH STEL 150 ppm OSHA TWA 100 ppm OSHA STEL 150 ppm	1330-20-7	5.10	68 F	4%
METHYLCYCLOHEXANE ACGIH TLV: 400 ppm TWA OSHA PEL: 400 ppm TWA	108-87-2	82.74	100 F	0-10%

* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 133 - 294.8 F	SPECIFIC GRAVITY (H ₂ O=1): 0.82
VAPOR DENSITY: Heavier than air	EVAPORATION RATE: Slower than ether
V.O.C. grams/liter: 840.72	V.O.C. lbs./gal.: 7.02
SOLUBILITY IN WATER: Insoluble	SOLIDS BY VOLUME: 0.00
APPEARANCE AND ODOR: Clear liquid with organic solvent odor	

M A T E R I A L S A F E T Y D A T A S H E E T

FS-5650

Page 5 of 8

===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

May cause nose and throat irritation. Repeated and prolonged exposure to organic solvents may lead to permanent brain and nervous system damage. Eye watering, headaches, nausea, dizziness, and loss of coordination are signs that solvent levels are too high.

Individuals with breathing problems must not be exposed to this product. If affected by inhalation, remove to fresh air. If breathing difficulty persists, consult a physician.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

May cause irritation or burning of the eyes. Repeated and prolonged skin contact may cause skin irritation or dermatitis. In case of eye contact, immediately flush eyes with plenty of water for at least 15 minutes; call a physician. In case of skin contact, wash with soap and water. If irritation occurs, contact a physician.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Gastrointestinal distress. In the unlikely event of ingestion, call a physician immediately and have the names of all ingredients available.

HEALTH HAZARDS (ACUTE AND CHRONIC)

ACUTE- Dizziness, irritation of the respiratory tract, weakness, nausea, or possible narcosis or even asphyxiation. May be accompanied by coughing or labored breathing.

CHRONIC- Reports have linked organic solvents with brain and nervous system damage. Misuse of this product by deliberately concentrating and inhaling the contents may be harmful or fatal.

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No

PROPOSITION 65 STATEMENT: WARNING! This product contains a chemical known to the state of California to cause birth defects or other reproductive harm.

OSHA REGULATED: Yes

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Do not use this product if you have chronic lung or breathing problems.

EMERGENCY AND FIRST AID PROCEDURES

If ingestion, or any type of overexposure or symptoms of overexposure occur during the use of this product, contact a poison control center, emergency room or physician immediately; have material safety data sheet available.

M A T E R I A L S A F E T Y D A T A S H E E T

FS-5650

Page 6 of 8

M A T E R I A L S A F E T Y D A T A S H E E T

FS-5650

Page 7 of 8

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition (sparks, flames, and hot surfaces). Avoid breathing vapors. Ventilate area. Remove with an inert absorbent and non-sparking tools.

WASTE DISPOSAL METHOD

Dispose in accordance with state ,federal and local regulations. Do not incinerate closed containers.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep containers tightly closed in a cool, dry, well ventilated area away from all possible ignition sources. Store large quantities of material in buildings designed for the storage of flammable liquids.

OTHER PRECAUTIONS

Employees should be trained in safety measures that should be taken when using this product.

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION

Avoid breathing vapors or spray mist. Wear a properly fitted respirator approved by NIOSH/MSHA (TC-23c) for use with paints during application and until all vapors are exhausted. In confined areas, or where continuous spray operations are typical, or proper respirator fit is not possible, wear a positive-pressure supplied air respirator (TC-19c). In all cases follow respirator manufactures directions for respirator use. Do not allow anyone without protection into the painting area.

VENTILATION

Provide sufficient ventilation to keep contaminates below applicable OSHA requirements.

PROTECTIVE GLOVES

Neoprene gloves impervious to organic solvents are recommended.

EYE PROTECTION

Use safety eyewear designed to protect against liquid splash.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Impervious coveralls are recommended.

WORK/HYGIENIC PRACTICES

M A T E R I A L S A F E T Y D A T A S H E E T

FS-5650

Page 8 of 8

Eye wash and safety showers in the work place are recommended. Wash hands before eating and smoking.

===== SECTION IX - DISCLAIMER =====

The information contained in this material safety data sheet is information from our suppliers and other sources. It is believed to be reliable. This data is not to be taken as a warranty or representation for which this company assumes legal responsibility.