

MATERIAL SAFETY DATA SHEET

5921  
02 00

Section 1 -- PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NUMBER 5921  
 PRODUCT NAME AeroPRO Paintable Undercoat  
 MANUFACTURER'S NAME Dist. by: International Autobody Marketing Group  
 Scottsdale, AZ 85261  
 DATE OF PREPARATION 12-APR-06  
 HMIS CODES Health 2\*, Flammability 4, Reactivity 0  
 EMERGENCY TELEPHONE NO. (216) 566-2917  
 INFORMATION TELEPHONE NO. (480) 451-4451

Section 2 -- COMPOSITION/INFORMATION ON INGREDIENTS

% by WT	CAS No.	INGREDIENT	UNITS	VAPOR PRESSURE
13	74-98-6	Propane	ACGIH TLV 2500 ppm OSHA PEL 1000 ppm	760 mm
6	106-97-8	Butane	ACGIH TLV 800 ppm OSHA PEL 800 ppm	760 mm
5	64742-89-8	V. M. & P. Naphtha	ACGIH TLV 300 ppm OSHA PEL 300 ppm OSHA PEL 400 ppm STEL	12 mm
13	108-88-3	Toluene	ACGIH TLV 50 ppm (Skin) OSHA PEL 100 ppm (Skin) OSHA PEL 150 ppm (Skin) STEL	22 mm
36	67-64-1	Acetone	ACGIH TLV 500 ppm ACGIH TLV 750 ppm STEL OSHA PEL 1000 ppm	180 mm
3	471-34-1	Calcium Carbonate	ACGIH TLV 10 mg/m3 as Dust OSHA PEL 15 mg/m3 Total Dust OSHA PEL 5 mg/m3 Respirable Fraction	
0.2	1333-86-4	Carbon Black	ACGIH TLV 3.5 mg/m3 OSHA PEL 3.5 mg/m3	

Section 3 -- HAZARDS IDENTIFICATION

ROUTES OF EXPOSURE  
 INHALATION of vapor or spray mist.  
 EYE or SKIN contact with the product, vapor or spray mist.

=====

EFFECTS OF OVEREXPOSURE

EYES: Irritation.

SKIN: Prolonged or repeated exposure may cause irritation.

INHALATION: Irritation of the upper respiratory system.

May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None generally recognized.

CANCER INFORMATION

For complete discussion of toxicology data refer to Section 11.

-----

Section 4 -- FIRST AID MEASURES

-----

EYES: Flush eyes with large amounts of water for 15 minutes.  
Get medical attention.

SKIN: Wash affected area thoroughly with soap and water.  
Remove contaminated clothing and launder before re-use.

INHALATION: If affected, remove from exposure. Restore breathing.  
Keep warm and quiet.

INGESTION: Do not induce vomiting.  
Get medical attention immediately.

-----

Section 5 -- FIRE FIGHTING MEASURES

-----

FLASH POINT	LEL	UEL
Propellant < 0 F	0.9	12.8

EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS

Containers may explode when exposed to extreme heat.

Application to hot surfaces requires special precautions.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used.

Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

-----

Section 6 -- ACCIDENTAL RELEASE MEASURES

-----

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate the area.

Remove with inert absorbent.

=====  
 Section 7 -- HANDLING AND STORAGE  
 -----

## STORAGE CATEGORY

Not Available

## PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may ignite explosively.

During use and until all vapors are gone: Keep area ventilated - Do not smoke - Extinguish all flames, pilot lights, and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition.

Consult NFPA Code. Use approved Bonding and Grounding procedures.

Contents under pressure. Do not puncture, incinerate, or expose to temperature above 120F. Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst. Do not take internally. Keep out of the reach of children.

 =====  
 Section 8 -- EXPOSURE CONTROLS/PERSONAL PROTECTION  
 -----

## PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation.

Avoid contact with skin and eyes. Avoid breathing vapor and spray mist.

Wash hands after using.

## VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

## RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

## PROTECTIVE GLOVES

None required for normal application of aerosol products where minimal skin contact is expected. For long or repeated contact, wear chemical resistant gloves.

## EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

## OTHER PRECAUTIONS

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

 =====  
 Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES  
 -----

PRODUCT WEIGHT	6.51 lb/gal	779 g/l
SPECIFIC GRAVITY	0.78	
BOILING POINT	<0 - 325 F	<-18 - 162 C
MELTING POINT	Not Available	
VOLATILE VOLUME	82 %	
EVAPORATION RATE	Faster than ether	
VAPOR DENSITY	Heavier than air	
SOLUBILITY IN WATER	N.A.	
VOLATILE ORGANIC COMPOUNDS (VOC Theoretical)		
Volatile Weight 38.06 %	Less Water and Federally Exempt Solvents	

Continued on page 4

=====  
 Section 10 -- STABILITY AND REACTIVITY  
 -----

STABILITY -- Stable

CONDITIONS TO AVOID

None known.

INCOMPATIBILITY

None known.

HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION

Will not occur  
 =====
 Section 11 -- TOXICOLOGICAL INFORMATION  
 -----

CHRONIC HEALTH HAZARDS

Carbon Black is classified by IARC as possibly carcinogenic to humans (group 2B) based on experimental animal data, however, there is insufficient evidence in humans for its carcinogenicity.

Prolonged overexposure to solvent ingredients in Section 2 may cause adverse effects to the liver, urinary, cardiovascular and reproductive systems.

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

 -----

TOXICOLOGY DATA

CAS No.	Ingredient Name					
74-98-6	Propane	LC50	RAT	4HR	Not Available	
		LD50	RAT		Not Available	
106-97-8	Butane	LC50	RAT	4HR	Not Available	
		LD50	RAT		Not Available	
64742-89-8	V. M. & P. Naphtha	LC50	RAT	4HR	Not Available	
		LD50	RAT		Not Available	
108-88-3	Toluene	LC50	RAT	4HR	4000	ppm
		LD50	RAT		5000	mg/kg
67-64-1	Acetone	LC50	RAT	4HR	Not Available	
		LD50	RAT		5800	mg/kg
471-34-1	Calcium Carbonate	LC50	RAT	4HR	Not Available	
		LD50	RAT		Not Available	
1333-86-4	Carbon Black	LC50	RAT	4HR	Not Available	
		LD50	RAT		Not Available	

 =====

 Section 12 -- ECOLOGICAL INFORMATION  
 -----

ECOTOXICOLOGICAL INFORMATION

No data available.

Continued on page 5

=====  
 Section 13 -- DISPOSAL CONSIDERATIONS  
 -----

## WASTE DISPOSAL METHOD

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Do not incinerate. Depressurize container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

 =====

 Section 14 -- TRANSPORT INFORMATION  
 -----

No data available.

 =====

 Section 15 -- REGULATORY INFORMATION  
 -----

## SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

CAS No.	CHEMICAL/COMPOUND	% by WT	% Element
108-88-3	Toluene	13	

 -----

## CALIFORNIA PROPOSITION 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

## TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

 =====

 Section 16 -- OTHER INFORMATION  
 -----

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.