

5 STAR MATERIAL SAFETY DATA SHEET : 09/04/08

-----  
ABI/ Autobody Brands International a division of IAMG/International  
Autobody Marketing Group  
9419 East San Salvador Drive Suite 104  
Scottsdale, AZ 85258  
Chemtrec (24 hours) 800-424-9300  
-----

Product: SUPERIOR RUBBERIZED UNDERCOAT- (VOC COMPLIANT)#5981C

-----  
SECTION 01: MANUFACTURER INFORMATION  
-----

MANUFACTURED FOR.....

ABI/ Autobody Brands International  
9419 East San Salvador Drive Suite 104  
Scottsdale, AZ 85258  
Chemtrec (24 hours) 800-424-9300

PRODUCT NAME.....SUPERIOR RUBBERIZED UNDERCOAT- VOC  
COMPLIANT

CHEMICAL FAMILY.....ORGANIC.

TRADE NAMES & SYNONYMS.....SAME AS PRODUCT NAME.

PRODUCT USES.....COATING.

LAB BOOK #.....008-2-387.

CHEMICAL FORMULA.....NOT APPLICABLE.

MOLECULAR WEIGHT.....NOT APPLICABLE.

T.D.G. CLASSIFICATION.....SHIPPING NAME: AEROSOL, UN: 1950, CLASS:  
2.1, PACKING GROUP: X.

WHMIS CLASSIFICATION.....A,B5,D2B.

CNFC SECTION 3.3.5.....LEVEL 2.

NFPA CODE 30B.....LEVEL 2.

HMIS RATING FLAMMABILITY.....4 SEVERE HAZARD.

HMIS RATING HEALTH.....2 MODERATE HAZARD.

HMIS RATING REACTIVITY.....0 MINIMAL HAZARD.

-----  
SECTION 02: HAZARDOUS INGREDIENTS  
-----

% CAS / TLV LD/50, ROUTE, SPECIES LC/50, ROUTE, SPECIES  
-----

ACETONE

10-30 67-64-1 >9750 mg/kg >16,000 ppm (4 hr)

750 ppm ORAL - RAT INHAL - RAT

TOLUENE

10-30 108-88-3 5000 mg/kg 8000 ppm (4 hr)

50 ppm ORAL - RAT INHAL - RAT

TALC (MAGNESIUM SILICATE HYDRATE)

5-10 14807-96-6 NOT AVAILABLE NOT AVAILABLE

2 mg/m<sup>3</sup>

ISOBUTANE

7-13 75-28-5 NOT APPLICABLE 142,500 ppm (4h)

INHAL - RAT

PROPANE

7-13 74-98-6 NOT APPLICABLE NOT AVAILABLE

1000 ppm  
-----

SECTION 03: PHYSICAL DATA

PHYSICAL STATE.....AEROSOL.  
VAPOUR PRESSURE(PSIG)-AEROSOL.....55 - 65.  
@ 20 C  
VAPOUR DENSITY (AIR=1).....GREATER THAN 1.  
(BY WEIGHT)  
SOLUBILITY IN WATER.....NEGLIGIBLE.  
APPEARANCE.....BLACK.  
ODOR.....AROMATIC ODOR.  
ODOR THRESHOLD.....NOT AVAILABLE.  
SPECIFIC GRAVITY (LIQUID).....0.97-0.98.  
(BY WEIGHT)  
EVAPORATION RATE.....GREATER THAN 1.  
n-BUTYL ACETATE = 1  
pH.....NOT APPLICABLE.  
FREEZING POINT: (C).....NOT AVAILABLE.  
COEFFICIENT OF WATER/OIL.....NOT AVAILABLE.  
DIST.

SECTION 04: FIRE & EXPLOSION DATA

AEROSOL FLAME PROJECTION  
CLASSIFIED AS:.....> 45 CM.  
FLAMMABILITY.....EXTREMELY FLAMMABLE.  
IF YES, UNDER WHICH.....EXCESSIVE HEAT, SPARKS AND OPEN  
FLAME.  
CONDITIONS ?  
EXTINGUISHING MEDIA.....CARBON DIOXIDE, DRY CHEMICAL, FOAM.  
SPECIAL PROCEDURES.....WATER FROM FOGGING NOZZLES MAY BE  
USED TO  
COOL CLOSED CONTAINERS TO PREVENT BUILD-UP  
IF EXPOSED TO EXTREME TEMPERATURES.FULL  
PROTECTIVE EQUIPMENT INCLUDING SELF  
CONTAINED BREATHING APPARTATUS SHOULD BE  
WORN IN A FIRE INVOLVING THIS MATERIAL.  
FLASH POINT (C), TAG CLOSED.....>-18.  
CUP  
AUTO IGNITION TEMPERATURE (C).....465 - 480.  
LOWER FLAMMABLE LIMIT.....1.  
(% BY VOLUME)  
UPPER FLAMMABLE LIMIT.....12.8.  
(% BY VOLUME)  
HAZARDOUS COMBUSTION  
PRODUCTS.....HYDROCARBON FUMES AND SMOKE. CARBON  
MONOXIDE WHERE COMBUSTION IS INCOMPLETE.  
EXPLOSION DATA  
SENSITIVITY TO STATIC.....NOT APPLICABLE.  
DISCHARGE  
SENSITIVITY TO IMPACT.....NOT APPLICABLE.

SECTION 05: REACTIVITY DATA

CHEMICAL STABILITY:

YES.....UNDER NORMAL CONDITIONS.  
NO, WHICH CONDITIONS?.....NOT APPLICABLE.  
COMPATABILITY WITH OTHER  
SUBSTANCES :  
NO, WHICH ONES?.....STRONG OXIDIZING AGENTS.  
HAZARDOUS PRODUCTS OF  
DECOMPOSITION.....HYDROCARBON FUMES AND SMOKE. CARBON  
MONOXIDE WHERE COMBUSTION IS INCOMPLETE.  
HAZARDOUS POLYMERIZATION.....WILL NOT OCCUR.  
REACTIVITY CONDITIONS?.....NOT APPLICABLE.

---

#### SECTION 06: TOXICOLOGICAL PROPERTIES

---

ROUTE OF ENTRY:  
SKIN CONTACT.....MAY CAUSE IRRITATION.  
SKIN ABSORPTION.....NO DATA AVAILABLE FOR THIS PRODUCT  
MIXTURE.  
EYE CONTACT.....MAY CAUSE IRRITATION.  
INHALATION.....INHALATION OF SOLVENTS MAY CAUSE  
IRRITATION. PROPELLANT IS A SIMPLE  
ASPHYXIANT.  
INGESTION.....MAY CAUSE HEADACHE, NAUSEA, VOMITING AND  
WEAKNESS.  
EFFECTS OF ACUTE EXPOSURE.....DIZZINESS, NAUSEA. IRRITATION TO  
SKIN &  
EYES.  
EFFECTS OF CHRONIC EXPOSURE.....SOLVENTS MAY CAUSE DEFATTING  
DERMATITIS.  
EXPOSURE LIMIT OF MATERIAL.....SEE SECTION II.  
IRRITANCY OF MATERIAL.....SKIN/EYE IRRITANT.  
SENSITIZING CAPABILITY OF.....UNKNOWN.  
MATERIAL  
CARCINOGENICITY OF MATERIAL.....THE INGREDIENTS OF THIS PRODUCT  
ARE NOT  
LISTED AS CARCINOGENS BY NTP, (NATIONAL  
TOXICOLOGY PROGRAM), NOT REGULATED AS  
CARCINOGENS BY OSHA, (OCCUPATIONAL SAFETY  
AND HEALTH ADMINISTRATION), AND HAVE NOT  
BEEN EVALUATED BY IARC,(INTERNATIONAL  
AGENCY FOR RESEARCH ON CANCER), NOR BY  
ACGIH (AMERICAN CONFERENCE OF GOVERNMENTAL  
INDUSTRIAL HYGIENISTS).  
REPRODUCTIVE EFFECTS.....TOLUENE - PROLONGED AND REPEATED  
EXPOSURE  
OF PREGNANT ANIMALS TO TOLUENE (LEVELS  
GREATER THAN APPROXIMATELY 1500 ppm) HAS  
BEEN REPORTED TO CAUSE ADVERSE FETAL  
DEVELOPMENTAL EFFECTS.  
TERATOGENICITY.....NO INFORMATION IS AVAILABLE AND NO  
ADVERSE  
TERATOGENIC EFFECTS ARE ANTICIPATED.  
MUTAGENICITY.....NO INFORMATION IS AVAILABLE AND NO  
ADVERSE  
MUTAGENIC EFFECTS ARE ANTICIPATED.

SYNERGISTIC MATERIALS.....NONE KNOWN.

---

SECTION 07: PREVENTIVE MEASURES

---

GLOVES/ TYPE.....WEAR CHEMICAL RESISTANT GLOVES.  
RESPIRATORY/TYPE.....IF USED INDOORS ON A CONTINUOUS BASIS,  
USE  
OF A CARTRIDGE TYPE RESPIRATOR  
(NIOSH/MSHATC 23C OR EQUIVALENT) IS  
RECOMMENDED.  
EYE/TYPE.....SAFETY GLASSES.  
FOOTWEAR/TYPE.....NOT NORMALLY REQUIRED.  
OTHER/TYPE.....NOT REQUIRED.  
ENGINEERING CONTROLS.....VENTILATION - LOCAL (MECHANICAL IF  
USED  
INDOORS ON A CONTINUOUS BASIS).  
LEAK/SPILL.....REMOVE ALL SOURCES OF IGNITION. USE AN  
INERT ABSORBENT MATERIAL, AND NON-SPARKING  
TOOLS. AVOID BREATHING FUMES. VENTILATE  
AREA. PREVENT FROM ENTERING A WATERCOURSE.  
HANDLING PROCEDURES AND  
EQUIPMENT.....STORE IN A COOL, WELL VENTILATED AREA NOT  
TO EXCEED 50 DEG C.  
WASTE DISPOSAL.....DO NOT PUNCTURE OR INCINERATE  
CONTAINERS,  
EVEN WHEN EMPTY.DIPOSE OF IN ACCORDANCE  
WITH LOCAL, PROVINCIAL AND FEDERAL  
REGULATIONS.  
STORAGE NEEDS.....KEEP AWAY FROM HEAT, SPARKS, AND OPEN  
FLAMES.  
SPECIAL SHIPPING INSTRUCTIONS.....SEE SECTION 1.....TDG  
CLASSIFICATION.

---

SECTION 08: FIRST AID MEASURES

---

EMERGENCY FIRST AID  
PROCEDURE.....IN CASE OF EYE CONTACT, FLUSH IMMEDIATELY  
WITH PLENTY OF WATER FOR AT LEAST 15  
MINUTES AND GET MEDICAL ATTENTION. FOR  
SKIN, WASH THOROUGHLY WITH SOAP AND WATER.  
IF AFFECTED BY INHALATION OF VAPOUR OR  
SPRAY MIST, REMOVE TO FRESH AIR. IF  
SWALLOWED; DO NOT INDUCE VOMITING, GET  
MEDICAL ATTENTION.

---

SECTION 09: ADDITIONAL INFORMATION

---

NOTICE FROM ABI/AUTOBODY BRANDS INTERNATIONAL  
CALIFORNIA-PROP 65 WARNING: THIS PRODUCT  
CONTAINS TRACE AMOUNTS OF BENZENE. A  
CHEMICAL KNOWN TO THE STATE OF CALIFORNIA  
TO CAUSE CANCER AND BIRTH DEFECTS, OR  
OTHER REPRODUCTIVE  
HARM.CALIFORNIA-CALIFORNIA PROPOSITION 65

WARNING: THIS PRODUCT CONTAINS TRACE AMOUNTS OF TOLUENE. TOLUENE-IS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.THE INFORMATION ON THIS MATERIAL SAFETY DATA SHEET IS PROVIDED BY ABI® AUTOBODY BRANDS INTERNATIONAL FREE OF CHARGE. WHILE BELIEVED TO BE RELIABLE, IT IS INTENDED FOR USE BY SKILLED PERSONS AT THEIR OWN RISK. ABI® AUTOBODY BRANDS INTERNATIONAL ASSUMES NO RESPONSIBILITY FOR EVENTS RESULTING OR DAMAGES INCURRED FROM ITS USE. THE INFORMATION ON THIS MATERIAL SAFETY DATA SHEET RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED HEREIN AND DOES NOT RELATE TO USE IN COMBINATION WITH ANY OTHER MATERIAL OR IN ANY PROCESS.

DATED.....09/04/08